

SP 88

SPECIFICATIONS

	U.S.	Metric
Concrete Output Per Hour	25 cu yds	19 cu m
Maximum Pressure on Concrete	500 psi	35 bar
Maximum Aggregate Size	0.5 in	13 mm
Concrete Cylinder Diameter	6 in	150 mm
Concrete Cylinder Stroke Length	6.5 in	165.1 mm
Differential Piston/Rod Diameter	N/A	N/A
Outlet Diameter	3 in	75 mm
Concrete Valve Type	Mechanical Ball	
Shifting Cylinders	N/A	
Max. Pump Strokes Per Minute	130	
Volume Control	40% to Maximum	
Hydraulic System	N/A	
Main Hydraulic Pump	N/A	
Hydraulic Pressure	N/A	N/A
Hydraulic Tank Capacity	N/A	N/A
Engine Model- Diesel Tier 4	CAT® C1.5 NA 3000 RPM	
Engine Power	33 hp	24.2 kW
Fuel Tank Capacity	18 gal	68 l
Hopper Capacity	7 cu ft	.2 cu m
Hopper-Height	54 in	1370 mm
Axle	Single Standard	
Axle Capacity Rating	3500 lbs	1588 kg
Tires	ST 205/75 R14	
Brakes	N/A	
Outrigger Legs	Manual Standard	
Length	12' 2"	3.7 m
Width	6' 4"	1.9 m
Height	6' 2"	1.9 m
Weight	2675 lbs	1213 kg
Dual Weight	N/A	N/A
Remote Control Cable	100 ft	30.5 m

*Pump specifications are for standard units. Other units are available.
Specifications are subject to change without prior notice.

